

LÄSSER MVD75 MINI MULTI DRIVE

MVD75 MINI
MULTI DRIVE



	MTC	needle and borer activated
	MTC CUT	needle and borer activated with cutting device
	ATC	needle, borer, thread roller and thread watcher device individually activated
	ATC CUT	needle, borer, single thread guide, thread roller, thread watcher device and shuttles individually activated with cutting device
Embroidery system	LÄSSER RH or LÄSSER LH	

Embroidery length [m]	1.5	
Embroidery length [yd]	1.6	
Number of embroidery positions	56	
Horizontal movement	100 / 4 repeat – 680 mm	128 / 4 repeat – 900 mm
Maximum speed (rpm)*	760	

* The speed is dependent on the embroidery height, the article to be manufactured, the yarns used and the operating conditions.

Machine length [m]	4.8	5.6
Net weight (approx.) [t]	2.4	2.8
Machine width [m]	1.8	

Embroidery height [m]	0.8	1.65
Machine height [m]	2.2	3.0
Height of the room [m]	2.3	3.1

Electric connection	3 x 400 V, +/-5% + PE, 50/60 Hz +/-2% A transformer is required if main voltage fluctuation are liable to occur.	
Pre-fusing	63 A time-delay 3 phases 4 x 16 mm ² (observe local regulations) PE always min. 16 mm ²	
Air pressure	NR / MTC 7 bar - 1 m ³ / hour ATC 7 bar - 2 m ³ / hour	
Maximum sound pressure	Leq = 79 dB (A) middle of needle side, distance to machine 1 meter, 1.60 meter above the ground	

Technical data MVD75 MINI EN
Technical changes reserved 01/25